



National Tel: 086 0022 157
 International Tel: +2741 581-0566

www.genesisacoustics.co.za

info@genesisacoustics.co.za
sales@genesisacoustics.co.za
brett@genesisacoustics.co.za
pa@genesisacoustics.co.za

Genesis 80D Acoustic Insulation Rolls
Spec Sheet
 January 2016

A proven, highly efficient sound absorbing product, due to its density & structure. The 80D comes in a roll which is flexible, it can be used on flat or curved surfaces for acoustic & thermal insulation. It reduces heat/loss gain for energy conservation.

The product is supported by a wire mesh, which can be used to fix the product in place by securing the edges with cable ties or wire. It is chemically neutral & will not cause or promote corrosion. It is biologically inert, it is unaffected by vermin & does not encourage the growth of fungi, moulds or bacteria.

- Non-flammable
- Density: 80kg/m³
- Roll width: 1200mm
- Thicknesses: 40, 50, 75 & 100mm

Roll sizes:				
40mm Thick	50mm Thick	75mm Thick	100mm Thick	-
1.2m x 5m	1.2m x 5m	1.2m x 3m	1.2m x 3m	-

Sound Absorption Coefficient at 40mm Thick: NRC 0.85				
125hz	250hz	500hz	1000hz	2000hz
0.17	0.49	0.85	0.99	0.99

- We deliver nationally, allow 3 working days.
- Lead Time for manufacture: normally 10 working days from date of order.